



## MON-DA0101-1 Mini Recessed LED Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

### SPOTLIGHT PARAMETERS Product Specification

|                       |                                              |
|-----------------------|----------------------------------------------|
| Workmanship           | Pure aluminium housing & integrated heatsink |
| Light Source          | CREE XP-E LED                                |
| Power                 | 1 W                                          |
| Color Rendering Index | Ra > 80                                      |
| Luminous Flux         | 91 lm (3000K)                                |
| Color Temperature     | 2700K / 3000K / 4000K / 6000K                |
| Beam Angle            | 12° / 20° / 30°                              |
| Driver                | Eaglerise ELP01SS · PF ≥ 0.50                |
| Input / Output        | AC 100–240 V 50-60 Hz · DC 350 mA 2.5–4 V    |
| Protection / Class    | IP20 · Class II · Cut-out Ø36 mm             |

### ACCESSORIES Options

-  Matte Black housing
-  Matte White housing
-  Honeycomb louver (anti-glare)
-  Frosted lens diffuser



Square recessed




Round recessed




Double recessed


### COLOR TEMPERATURE




2700K



3000K




4000K




6000K


### BEAM ANGLE



12°



20°



30°

### USAGE SPACES

-  Showcase & display cabinets
-  Residential accent lighting
-  Commercial spaces

### DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



Ceiling cut-out: Ø36 mm

Inner box: 7 × 7 × 5 cm

Carton: 37 × 30 × 32 cm · 80 pcs/ctn