



MON-DB0101-1 Mini Recessed LED Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Workmanship	Pure aluminium housing & integrated heatsink
Light Source	Luminus LED
Power	1 W
Color Rendering Index	Ra > 95
Luminous Flux	91 lm (3000K)
Color Temperature	2700K / 3000K / 4000K / 6000K
Beam Angle	12° / 20° / 30°
Driver	Eaglerise ELP01SS · PF ≥ 0.50
Input / Output	AC 100–240 V 50-60 Hz · DC 350 mA 2.5–4 V
Protection / Class	IP20 · Class II · Cut-out Ø30 mm

ACCESSORIES Options

-  Matte Black housing
-  Matte White housing
-  Honeycomb louver (anti-glare)
-  Frosted lens diffuser



Square recessed




Round recessed




Double recessed


COLOR TEMPERATURE




2700K



3000K




4000K




6000K


BEAM ANGLE



12°



20°




30°

USAGE SPACES

-  Showcase & display cabinets
-  Residential accent lighting
-  Commercial spaces

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



cut-out Ø30 mm

Ceiling cut-out: Ø30 mm

Inner box: 7 × 7 × 5 cm

Carton: 37 × 30 × 32 cm · 80 pcs/ctn