

Product Description

This downlight series focus on the minimal appearance, giving stage to the light instead of the fixture. The fixture surface is treated by powder coating, making for a durable color, meeting the stylistic demands of different environments. It offers high anti-glare technology, high lighting efficiency and choice of dimensions and optical angles to fully satisfy all the different lighting effects.

Product Specification

Luminaire Wattage	3W
Luminaire Color	☐ White ☒ Black
Light Source	LUMINUS
Color Temperature	2700K/3000K/4000K
Color Rendering Index	Ra>95
Beam Angle	15°/24°/30°
Luminous Flux	100lm at 3000K
cut-out	Ø30MM
Driver	ELP03SS1
Power Factor (PF)	≥0.50
Input	AC100-240V 50-60Hz
Output	DC 700mA 2.5-4V
Class	II
IP Degree	IP20
Inner Box	7X7X5cm
Carton Size	37X30X32cm
QTY/CTN	80PCS/CTN
Net Weight	0.1KG/PCS


Model No.

MON-DB0401-2





Light Distribution

3000K 15°




h(m)	E(lx)	D(m)
1	1087	0.30
2	271	0.61
3	120	0.91
4	67	1.22

3000K 24°



h(m)	E(lx)	D(m)
1	397	0.47
2	99	0.94
3	44	1.41
4	24	1.88

3000K 30°



h(m)	E(lx)	D(m)
1	343	0.50
2	85	1.00
3	38	1.50
4	21	2.00

Related references

Optional Accessories



Honeycomb

Size: 17×3



Combed Glass

Size: 17×3



Woven Glass

Size: 17×3

Related references

LED POWER SUPPLIES



Constant current power supply

Brand: Eaglerise

Triac

0-10V

Dali

Related project picture of product family:

