

Product Description


This downlight series focus on the minimal appearance, giving stage to the light instead of the fixture. The fixture surface is treated by powder coating, making for a durable color, meeting the stylistic demands of different environments. It offers high anti-glare technology, high lighting efficiency and choice of dimensions and optical angles to fully satisfy all the different lighting effects.

Product Specification

Luminaire Wattage	6W
Luminaire Color	☐ White ☒ Black
Light Source	Luminus CXM-6
Color Temperature	2700K/3000K/4000K/5000K
Color Rendering Index	Ra>90
Beam Angle	24°/36°
Luminous Flux	320lm at 3000K
cut-out	Ø50MM
Driver	LS-8-150 SI1
Power Factor (PF)	≥0.50
Input	AC220-240V 50-60Hz
Output	DC150mA 36V
Class	II
IP Degree	IP20
Inner Box	7X7X8.5cm
Carton Size	37X30X36cm
QTY/CTN	80PCS/CTN
Net Weight	0.16KG/PCS


Model No.

MON-DB0406-C





Light Distribution

3000K 24°



3000K 36°



Related references

Optional Accessories



Honeycomb

Size: 33×3



Combed Glass

Size: 33×3



Woven Glass

Size: 33×3

Related references

LED POWER SUPPLIES



Constant current power supply

Triac

0-10V

Dali

Brand: Eaglerise

Related project picture of product family:

