

Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/6/2026

Tested c-planes	8
Tested gamma angles	181 – 1.00°
Input Power	7.11 W

Luminaire	2021/6/26 16:55:14
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Output — Total Lumen (Up% / Down%)	336.7 lm — 0.0003% / 100%
Efficiency	47.36 lm/W
Peak Intensity	1732 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index	CRI 85.0

cd

— C0 - C180
— C90 - C270


$\eta = 99.88\%$

Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Low (0-30°)	184.5 lm	54.8%
Medium (30-60°)	6.5 lm	1.9%
High (60-80°)	0.8 lm	0.2%
Very High (80-90°)	0.3 lm	0.1%

Back Light

Low (0-30°)	139.2 lm	41.3%
Medium (30-60°)	4.6 lm	1.4%
High (60-80°)	0.6 lm	0.2%
Very High (80-90°)	0.2 lm	0.1%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	336.7 lm	100,0%
-----	----------	--------