

Laboratory and Equipment

Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/14/2026

Measurement Conditions

Tested c-planes	12
Tested gamma angles	181 – 1.00°
Input Power	1.72 W


Tested Light Source

Luminaire	2022/10/20 16:06:03
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	58.78 lm – 0% / 100%
Efficiency	34.17 lm/W
Peak Intensity	126 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index	CRI 85.0

Polar light distribution diagram




Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B0 U0 G0



Forward Light

Low (0-30°)	26.2 lm	44.6%
Medium (30-60°)	5.5 lm	9.3%
High (60-80°)	0.4 lm	0.6%
Very High (80-90°)	0.0 lm	0.0%

Back Light

Low (0-30°)	21.8 lm	37.1%
Medium (30-60°)	4.5 lm	7.6%
High (60-80°)	0.4 lm	0.7%
Very High (80-90°)	0.0 lm	0.0%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	58.8 lm	100,0%
-----	---------	--------