



MON-DD1001-35 Adjustable Recessed LED Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Light Source	Luminus SST-20 LED module
Power	3.7 W
Luminous Flux	53 lm (3000K)
Light Effect	14.3 lm/W
Color Rendering Index	Ra ≥ 95
Color Temperature	2700K / 3000K / 4000K / 5000K
Beam Angle	15°
Driver	PE-091B04120 · PF ≥ 0.5
Input / Output	AC 220-240V 50-60Hz · DC 1200mA 2-4V
Protection / Class	IP20 · Class II · Cut-out Ø35 mm

ACCESSORIES Options



White housing



Black housing



Dimmable driver options: Triac / 0-10V / DALI



Honeycomb anti-glare louver



Round recessed




Adjustable tilt




Trim / trimless


COLOR TEMPERATURE




2700K



3000K



4000K



5000K

BEAM ANGLE



15°

USAGE SPACES



HOME

Residential accent lighting



RETAIL

Shops & display niches



HOTEL

Hospitality & galleries

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



cut-out Ø35 mm

Ceiling cut-out: Ø35 mm

Inner box: 5 × 5 × 5 cm

Carton: 27.5 × 27.5 × 22.5 cm · 125 pcs/ctn

Net weight: 0.065 kg/pc