



## MON-G3A-2 Recessed LED Grille Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

### PRODUCT PARAMETERS Specification

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Light Source          | SMD3535 LED · Herculux precision lens         |
| Light Heads           | 2 × module                                    |
| Power                 | max. 4 W                                      |
| Color Rendering Index | Ra > 90                                       |
| Color Temperature     | 2700K – 5000K (2700K / 3000K / 4000K / 5000K) |
| Beam Angle            | 15° / 25° / 35° / 50°                         |
| Driver Options        | ON/OFF · 0-10V · DALI · Tuya Smart            |
| Dimensions            | 70.5 × 32 × 58 mm                             |
| Ceiling Cut-out       | 63 × 25 mm                                    |
| Housing               | White / Black · aluminum                      |
| Accessories           | Honeycomb anti-glare optics                   |

### OPTIONS Configure to order

- ☐ White housing
- ☐ Black housing
- ☐ Driver: ON/OFF / 0-10V / DALI / Tuya Smart
- ☐ Honeycomb anti-glare louver
- ☐ CCT options: 2700K / 3000K / 4000K / 5000K



Recessed




Square aperture




Trim / trimless


### COLOR TEMPERATURE




2700K



3000K




4000K




5000K


### BEAM ANGLE




15°



25°



35°




50°

### USAGE SPACES

- HOME** Residential accent lighting
- RETAIL** Shops & display niches
- HOTEL** Hospitality & galleries

### DIMENSIONS unit: mm (untoleranced dimensions ±0.5 mm)



cut-out 63 × 25 mm

Body: 70.5 × 32 × 58 mm  
 Ceiling cut-out: 63 × 25 mm  
 Material: die-cast aluminum  
 Finish: white or black, matt