




MON-G3A-8 Recessed LED Grille Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

PRODUCT PARAMETERS Specification

Light Source	SMD3535 LED · Herculux precision lens
Light Heads	8 × module
Power	max. 16 W
Color Rendering Index	Ra > 90
Color Temperature	2700K – 5000K (2700K / 3000K / 4000K / 5000K)
Beam Angle	15° / 25° / 35° / 50°
Driver Options	ON/OFF · 0-10V · DALI · Tuya Smart
Dimensions	245 × 32 × 58 mm
Ceiling Cut-out	240 × 25 mm
Housing	White / Black · aluminum
Accessories	Honeycomb anti-glare optics

OPTIONS Configure to order

- ☐ White housing
- ☐ Black housing
- ☐ Driver: ON/OFF / 0-10V / DALI / Tuya Smart
- ☐ Honeycomb anti-glare louver
- ☐ CCT options: 2700K / 3000K / 4000K / 5000K



Recessed




Square aperture




Trim / trimless


COLOR TEMPERATURE




2700K



3000K




4000K




5000K


BEAM ANGLE




15°



25°



35°




50°

USAGE SPACES

- HOME** Residential accent lighting
- RETAIL** Shops & display niches
- HOTEL** Hospitality & galleries

DIMENSIONS unit: mm (untoleranced dimensions ±0.5 mm)



cut-out 240 × 25 mm

Body: 245 × 32 × 58 mm
Ceiling cut-out: 240 × 25 mm
Material: die-cast aluminum
Finish: white or black, matt