



MON-G4E-1 Recessed LED Grille Spotlight

✓ CE Certified

✓ RoHS Compliant


✓ Flicker-free

PRODUCT PARAMETERS Specification

Light Source	SMD3535 LED · Ledlink precision lens
Light Heads	1 × module
Power	max. 3 W
Color Rendering Index	Ra > 90
Color Temperature	2700K – 5000K (2700K / 3000K / 4000K / 5000K)
Beam Angle	10° / 15° / 25° / 35°
Driver Options	ON/OFF · 0-10V · DALI · Tuya Smart
Dimensions	31.5 × 31.5 × 55 mm
Ceiling Cut-out	25 × 25 mm
Housing	White / Black · aluminum
Accessories	Honeycomb anti-glare optics

OPTIONS Configure to order

- ☐ White housing
- ☐ Black housing
- ☐ Driver: ON/OFF / 0-10V / DALI / Tuya Smart
- ☐ Honeycomb anti-glare louver
- ☐ CCT options: 2700K / 3000K / 4000K / 5000K



COLOR TEMPERATURE




BEAM ANGLE



USAGE SPACES

- HOME** Residential accent lighting
- RETAIL** Shops & display niches
- HOTEL** Hospitality & galleries

DIMENSIONS unit: mm (untoleranced dimensions ±0.5 mm)



Body: 31.5 × 31.5 × 55 mm
 Ceiling cut-out: 25 × 25 mm
 Material: die-cast aluminum
 Finish: white or black, matt