



MON-G4H-3 Recessed LED Grille Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

PRODUCT PARAMETERS Specification

Light Source	SMD3535 LED · Herculux precision lens
Light Heads	3 × module
Power	max. 8 W
Color Rendering Index	Ra > 90
Color Temperature	2700K – 5000K (2700K / 3000K / 4000K / 5000K)
Beam Angle	40° / 60° / 80°
Driver Options	ON/OFF · 0-10V · DALI · Tuya Smart
Dimensions	75 × 31.5 × 56 mm
Ceiling Cut-out	69 × 25 mm
Housing	White / Black · aluminum

OPTIONS Configure to order

- ☐ White housing
- ☐ Black housing
- ☐ Driver: ON/OFF / 0-10V / DALI / Tuya Smart
- ☐ Honeycomb anti-glare louver
- ☐ CCT options: 2700K / 3000K / 4000K / 5000K



Recessed




Square aperture




Trim / trimless


COLOR TEMPERATURE




2700K



3000K




4000K




5000K


BEAM ANGLE



40°



60°




80°

USAGE SPACES

- HOME** Residential accent lighting
- RETAIL** Shops & display niches
- HOTEL** Hospitality & galleries

DIMENSIONS unit: mm (untoleranced dimensions ±0.5 mm)



cut-out 69 × 25 mm

Body: 75 × 31.5 × 56 mm
 Ceiling cut-out: 69 × 25 mm
 Material: die-cast aluminum
 Finish: white or black, matt