



MON-PL3162A Adjustable Recessed LED Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

PRODUCT PARAMETERS Specification

Light Source	SMD3535 LED
Power	max. 2 W
Color Rendering Index	Ra > 90
Color Temperature	2700K – 5000K (2700K / 3000K / 4000K / 5000K)
Beam Angle	15° / 40° (focusable)
Driver Options	ON/OFF · 0-10V · DALI · Tuya Smart
Dimensions	Ø31 × H62 mm
Ceiling Cut-out	Ø25 mm
Housing	White / Black · aluminum

OPTIONS Configure to order

- ☐ White housing
- ☐ Black housing
- ☐ Driver: ON/OFF / 0-10V / DALI / Tuya Smart
- ☐ Honeycomb anti-glare louver
- ☐ CCT options: 2700K / 3000K / 4000K / 5000K



Recessed




Square aperture




Trim / trimless


COLOR TEMPERATURE




2700K



3000K



4000K



5000K

BEAM ANGLE



15°




40°

USAGE SPACES

- HOME** Residential accent lighting
- RETAIL** Shops & display niches
- HOTEL** Hospitality & galleries

DIMENSIONS unit: mm (untoleranced dimensions ±0.5 mm)



cut-out Ø25 mm

Body: Ø31 × H62 mm
Ceiling cut-out: Ø25 mm
Material: die-cast aluminum
Finish: white or black, matt