



MON-PR3556 Adjustable Recessed LED Spotlight

✓ CE Certified

✓ RoHS Compliant


✓ Flicker-free

PRODUCT PARAMETERS Specification

Light Source	SMD3535 LED · Ledlink precision lens
Power	max. 3 W
Color Rendering Index	Ra > 90
Color Temperature	2700K – 5000K (2700K / 3000K / 4000K / 5000K)
Beam Angle	10° / 15° / 25° / 35° / 50°
Driver Options	ON/OFF · 0-10V · DALI · Tuya Smart
Dimensions	Ø35 × H56 mm
Ceiling Cut-out	Ø30 mm
Housing	White / Black · aluminum
Accessories	Honeycomb anti-glare optics

OPTIONS Configure to order


- ☐ White housing
- ☐ Black housing
- ☐ Driver: ON/OFF / 0-10V / DALI / Tuya Smart
- ☐ Honeycomb anti-glare louver
- ☐ CCT options: 2700K / 3000K / 4000K / 5000K



COLOR TEMPERATURE




BEAM ANGLE



USAGE SPACES

- ☐ HOME Residential accent lighting
- ☐ RETAIL Shops & display niches
- ☐ HOTEL Hospitality & galleries

DIMENSIONS unit: mm (untoleranced dimensions ±0.5 mm)



Body: Ø35 × H56 mm
 Ceiling cut-out: Ø30 mm
 Material: die-cast aluminum
 Finish: white or black, matt