


Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/14/2026

Tested c-planes	8
Tested gamma angles	181 – 1.00°
Input Power	28.52 W

Output — Total Lumen (Up% / Down%)	1381 lm — 0.0031% / 100%
Efficiency	48.43 lm/W
Peak Intensity	8606 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index	CRI 85.0


[illegible]

Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U0 G0



Forward Light

Low (0-30°)	644.1 lm	46.6%
Medium (30-60°)	36.3 lm	2.6%
High (60-80°)	11.5 lm	0.8%
Very High (80-90°)	5.7 lm	0.4%

Back Light

Low (0-30°)	630.5 lm	45.6%
Medium (30-60°)	35.7 lm	2.6%
High (60-80°)	11.6 lm	0.8%
Very High (80-90°)	5.7 lm	0.4%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	1381.3 lm	100,0%
-----	-----------	--------