



MON-SA1040-C Recessed LED Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Light Source	HRB1430 LED module
Power	40 W
Luminous Flux	1800 lm (3000K)
Light Effect	45.0 lm/W
Color Rendering Index	Ra ≥ 95
Color Temperature	2700K / 3000K
Beam Angle	15° / 24° / 36°
Driver	LS-8-900 S11 · PF ≥ 0.5
Input / Output	AC 220-240V 50-60Hz · DC 900mA 30-42V
Protection / Class	IP20 · Class I


ACCESSORIES Options

- ☐ White housing
 - ☐ Black housing
 - ☐ Dimmable driver options: Triac / 0-10V / DALI
 - ☐ Asymmetric wall-washer lens
-  Round recessed
  Adjustable tilt
  Trim / trimless

COLOR TEMPERATURE



BEAM ANGLE



USAGE SPACES

- HOME** Residential accent lighting
- RETAIL** Shops & commercial spaces
- HOTEL** Hospitality & galleries

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



Inner box: 20.5 × 18 × 19 cm
 Carton: 55.5 × 42.5 × 39.5 cm · 12 pcs/ctn
 Net weight: 0.6 kg/pc