



MON-SA2315-C Recessed LED Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Light Source	HRA0610 LED module
Power	15 W
Luminous Flux	1093 lm (3000K)
Light Effect	72.9 lm/W
Color Rendering Index	Ra ≥ 95
Color Temperature	2700K / 3000K / 4000K / 5000K
Beam Angle	15° / 24° / 36° / 50°
Driver	LS-12-350 SI ECO · PF ≥ 0.50
Input / Output	AC 220-240V 50/60Hz · DC 36V 350mA
Protection / Class	IP20 · Class II · Cut-out Ø75 mm

ACCESSORIES Options



White housing



Black housing



Dimmable driver options: Triac / 0-10V / DALI



Asymmetric wall-washer lens



Round recessed




Adjustable tilt




Trim / trimless


COLOR TEMPERATURE




2700K



3000K




4000K



5000K

BEAM ANGLE



15°



24°



36°



50°

USAGE SPACES



HOME Residential accent lighting



RETAIL Shops & commercial spaces



HOTEL Hospitality & galleries

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



cut-out Ø75 mm

Ceiling cut-out: Ø75 mm

Inner box: 11 × 11 × 9.5 cm

Carton: 46 × 24 × 31 cm · 24 pcs/ctn

Net weight: 0.3 kg/pc