


Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/14/2026

Tested c-planes	8
Tested gamma angles	181 – 1.00°
Input Power	23.81 W

Luminaire	2021/4/15 15:45:54
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Output — Total Lumen (Up% / Down%)	1945 lm — 0.002% / 100%
Efficiency	81.69 lm/W
Peak Intensity	15.94 kcd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index	CRI 85.0

Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U0 G0



Forward Light

Low (0-30°)	739.5 lm	38.0%
Medium (30-60°)	252.0 lm	13.0%
High (60-80°)	28.8 lm	1.5%
Very High (80-90°)	6.2 lm	0.3%

Back Light

Low (0-30°)	662.3 lm	34.1%
Medium (30-60°)	224.4 lm	11.5%
High (60-80°)	26.1 lm	1.3%
Very High (80-90°)	5.7 lm	0.3%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	1945.1 lm	100,0%
-----	-----------	--------