

Laboratory and Equipment

Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/14/2026

Measurement Conditions

Tested c-planes	8
Tested gamma angles	181 – 1.00°
Input Power	27.6 W


Tested Light Source

Luminaire	2021/4/18 8:24:18
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	2417 lm – 0.0016% / 100%
Efficiency	87.56 lm/W
Peak Intensity	4579 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index	CRI 85.0

Polar light distribution diagram




Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U0 G0



Forward Light

Low (0-30°)	994.6 lm	41.2%
Medium (30-60°)	190.5 lm	7.9%
High (60-80°)	53.8 lm	2.2%
Very High (80-90°)	10.1 lm	0.4%

Back Light

Low (0-30°)	943.2 lm	39.0%
Medium (30-60°)	164.7 lm	6.8%
High (60-80°)	51.0 lm	2.1%
Very High (80-90°)	8.8 lm	0.4%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	2416.8 lm	100,0%
-----	-----------	--------