

Laboratory and Equipment

Test lab	EVERFINE
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/14/2026

Measurement Conditions

Tested c-planes	24
Tested gamma angles	361 – 0.50°
Input Power	42.6 W


Tested Light Source

Luminaire	
Basic Luminous Shape	SPOT
Item No.	
Manufacturer	Moon On Noon


Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	2726 lm – 0.1771% / 99.82%
Efficiency	63.98 lm/W
Peak Intensity	4766 cd
Correlated Color Temperature, CCT	2700 K
Color Rendering Index	CRI 85.0

Polar light distribution diagram




Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B2 U1 G0



Forward Light

Low (0-30°)	1027.2 lm	37.7%
Medium (30-60°)	351.0 lm	12.9%
High (60-80°)	28.2 lm	1.0%
Very High (80-90°)	1.3 lm	0.0%

Back Light

Low (0-30°)	968.4 lm	35.5%
Medium (30-60°)	317.1 lm	11.6%
High (60-80°)	26.8 lm	1.0%
Very High (80-90°)	0.9 lm	0.0%

Uplight

Low (90-100°)	0.4 lm	0.01%
High (100-180°)	4.5 lm	0.2%

Total

Sum	2725.7 lm	100,0%
-----	-----------	--------