


Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/14/2026

Tested c-planes	8
Tested gamma angles	181 – 1.00°
Input Power	10.48 W

Luminaire	2021/4/22 20:44:06
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Output — Total Lumen (Up% / Down%)	474 lm — 0.0005% / 100%
Efficiency	45.23 lm/W
Peak Intensity	1766 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index	CRI 85.0

Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Low (0-30°)	224.5 lm	47.4%
Medium (30-60°)	15.6 lm	3.3%
High (60-80°)	0.9 lm	0.2%
Very High (80-90°)	0.4 lm	0.1%

Back Light

Low (0-30°)	216.1 lm	45.6%
Medium (30-60°)	15.2 lm	3.2%
High (60-80°)	0.9 lm	0.2%
Very High (80-90°)	0.4 lm	0.1%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	474.0 lm	100,0%
-----	----------	--------