


Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/14/2026

Tested c-planes	12
Tested gamma angles	$181 - 1.00^\circ$
Input Power	6.52 W

Luminaire	2023/4/25 10:18:00
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Output	—	Total Lumen (Up% / Down%)	475.7 lm	—	0.0005% / 100%
Efficiency			72.96 lm/W		
Peak Intensity			1264 cd		
Correlated Color Temperature, CCT			3000 K		
Color Rendering Index			CRI 85.0		

Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Low (0-30°)	224.3 lm	47.1%
Medium (30-60°)	18.9 lm	4.0%
High (60-80°)	0.9 lm	0.2%
Very High (80-90°)	0.4 lm	0.1%

Back Light

Low (0-30°)	213.7 lm	44.9%
Medium (30-60°)	16.0 lm	3.4%
High (60-80°)	1.0 lm	0.2%
Very High (80-90°)	0.5 lm	0.1%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	475.7 lm	100,0%
-----	----------	--------