



MON-SB2307-N Recessed LED Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Light Source	Honour HRA0607 LED module
Power	7 W
Luminous Flux	464 lm (3000K)
Light Effect	66.3 lm/W
Color Rendering Index	Ra ≥ 95
Color Temperature	2700K / 3000K / 4000K / 5000K
Beam Angle	15° / 24° / 36°
Driver	LS-8-150 SI ECO · PF ≥ 0.50
Input / Output	AC 220-240V 50-60Hz · DC 36V 150mA
Protection / Class	IP20 · Class II · Cut-out Ø55 mm

ACCESSORIES Options



White housing



Black housing



Dimmable driver options: Triac / 0-10V / DALI



Asymmetric wall-washer lens



Round recessed




Adjustable tilt




Trim / trimless


COLOR TEMPERATURE




2700K



3000K




4000K




5000K


BEAM ANGLE



15°



24°



36°

USAGE SPACES



Residential accent lighting



Shops & commercial spaces



Hospitality & galleries

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



cut-out Ø55 mm

Ceiling cut-out: Ø55 mm

Inner box: 10 × 10 × 7 cm

Carton: 42 × 32 × 30 cm · 48 pcs/ctn

Net weight: 0.19 kg/pc