



MON-SB2415-C Recessed LED Downlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Light Source	V10C LED module
Power	15 W
Luminous Flux	1500 lm (3000K)
Light Effect	100.0 lm/W
Color Rendering Index	Ra ≥ 95
Color Temperature	2700K / 3000K / 4000K / 5000K
Beam Angle	15° / 24° / 36° / 50°
Driver	BK-PPL018-B0350A · PF ≥ 0.9
Input / Output	AC 220-240V 50-60Hz · DC 350mA 28-42V
Protection / Class	IP65 · Class I

ACCESSORIES Options

-  White housing
-  Black housing
-  Dimmable driver options: Triac / 0-10V / DALI
-  Honeycomb anti-glare louver



Round recessed




Fixed downlight




Trim / trimless


COLOR TEMPERATURE




2700K



3000K




4000K



5000K

BEAM ANGLE




15°



24°



36°



50°

USAGE SPACES

-  Residential accent lighting
-  Shops & display niches
-  Hospitality & galleries

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



recessed installation

Inner box: 12 × 12 × 10 cm

Carton: 50 × 26 × 32 cm · 24 pcs/ctn