

Light measurement report



Laboratory and Equipment

Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	7/14/2026

Measurement Conditions

Tested c-planes	12
Tested gamma angles	181 – 1.00°
Input Power	23.83 W


Tested Light Source

Luminaire	2023/5/10 15:18:33
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	2552 lm – 0.001% / 100%
Efficiency	107.1 lm/W
Peak Intensity	5404 cd
Correlated Color Temperature, CCT	2700 K
Color Rendering Index	CRI 85.0

Polar light distribution diagram




Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B3 U0 G0



Forward Light

Low (0-30°)	1162.0 lm	45.5%
Medium (30-60°)	104.7 lm	4.1%
High (60-80°)	8.9 lm	0.3%
Very High (80-90°)	4.3 lm	0.2%

Back Light

Low (0-30°)	1155.3 lm	45.3%
Medium (30-60°)	102.7 lm	4.0%
High (60-80°)	9.1 lm	0.4%
Very High (80-90°)	4.5 lm	0.2%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	2551.6 lm	100,0%
-----	-----------	--------