



MON-SB2425-C Recessed LED Downlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Light Source	V13C LED module
Power	25 W
Luminous Flux	2500 lm (3000K)
Light Effect	100.0 lm/W
Color Rendering Index	Ra ≥ 95
Color Temperature	2700K / 3000K / 4000K / 5000K
Beam Angle	15° / 24° / 36° / 50°
Driver	BK-PPL022-B0600A · PF ≥ 0.9
Input / Output	AC 220-240V 50-60Hz · DC 600mA 28-38V
Protection / Class	IP65 · Class I

ACCESSORIES Options



White housing



Black housing



Dimmable driver options: Triac / 0-10V / DALI



Honeycomb anti-glare louver



Round recessed




Fixed downlight




Trim / trimless


COLOR TEMPERATURE




2700K



3000K




4000K



5000K

BEAM ANGLE




15°



24°



36°



50°

USAGE SPACES



Residential accent lighting



Shops & display niches



Hospitality & galleries

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



recessed installation

Inner box: 12 × 12 × 12 cm

Carton: 49.5 × 25.5 × 38 cm · 24 pcs/ctn