



MON-SR2203-N

Asymmetric Wall Washer Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Light Source	Luminus SST20 LED module
Power	3 W
Luminous Flux	52 lm (3000K)
Light Effect	17.3 lm/W
Colour Rendering Index	Ra ≥ 95
Colour Temperature	2700 / 3000 / 4000 / 5000K
Beam Angle	65° × 72° (Asymmetric)
Driver	LS-3-700 SI · PF ≥ 0.50
Input / Output	AC 220-240V 50-60Hz · DC 700mA
Protection / Class	IP20 · Class II · Cut-out Ø75 mm

ACCESSORIES Options

- ☐ White housing
- ☒ Black housing
- ☐ Dimmable driver: Triac / 0-10V / DALI
- ☐ Asymmetric wall-washer reflector



COLOR TEMPERATURE




BEAM ANGLE



USAGE SPACES

- WALL** Wall washing & facades
- RETAIL** Shops & galleries
- HOTEL** Hospitality lobbies

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



Ceiling cut-out: Ø75 mm
Inner box: 10 × 10 × 7 cm
Carton: 42 × 32 × 30 cm · 48 pcs/ctn
Net weight: 0.25 kg/pc