


Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	6/26/2026

Tested c-planes	8
Tested gamma angles	181 – 1.00°
Input Power	6.29 W

Luminaire	2021/12/23 8:43:19
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Output	—	Total Lumen (Up% / Down%)	541.3 lm	—	0.0007% / 100%
Efficiency			86.05 lm/W		
Peak Intensity			2512 cd		
Correlated Color Temperature, CCT			3000 K		
Color Rendering Index			CRI 85.0		

Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Low (0-30°)	281.7 lm	52.0%
Medium (30-60°)	10.8 lm	2.0%
High (60-80°)	1.8 lm	0.3%
Very High (80-90°)	0.7 lm	0.1%

Back Light

Low (0-30°)	234.4 lm	43.3%
Medium (30-60°)	9.4 lm	1.7%
High (60-80°)	1.8 lm	0.3%
Very High (80-90°)	0.7 lm	0.1%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	541.3 lm	100,0%
-----	----------	--------