



MON-SS2210-N

Adjustable Recessed Spotlight

✓ CE Certified

✓ RoHS Compliant

✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification

Light Source	HonourTEK HRA0607 LED
Power	10 W
Luminous Flux	611 lm (3000K)
Light Effect	61.1 lm/W
Colour Rendering Index	Ra ≥ 95
Colour Temperature	2700 / 3000 / 4000 / 5000K
Beam Angle	15° / 24° / 36° / 50°
Driver	LS-12-250 SI3 · PF ≥ 0.50
Input / Output	AC 220-240V 50-60Hz · DC 250mA
Protection / Class	IP20 · Class II · Cut-out Ø75 mm

ACCESSORIES Options


- ☐ White housing
- ☒ Black housing
- ☐ Dimmable driver: Triac / 0-10V / DALI
- ☐ Optional lens / anti-glare accessories



COLOR TEMPERATURE




BEAM ANGLE



USAGE SPACES

- HOME** Residential accent lighting
- RETAIL** Shops & commercial spaces
- HOTEL** Hospitality & galleries

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



Ceiling cut-out: Ø75 mm
Inner box: 10 × 10 × 8.5 cm
Carton: 42 × 32 × 27.5 cm · 36 pcs/ctn
Net weight: 0.18 kg/pc