



MON-SU2208-N

Adjustable Recessed Spotlight

✓ CE Certified

✓ RoHS Compliant


✓ Flicker-free

SPOTLIGHT PARAMETERS Product Specification



Light Source	HonourTEK HRA0607 LED
Power	8 W
Luminous Flux	664 lm (2700K)
Light Effect	83.0 lm/W
Colour Rendering Index	Ra ≥ 95
Colour Temperature	2700 / 3000 / 4000 / 5000K
Beam Angle	15° / 24° / 36° / 50°
Driver	LS-8-200 SI ECO · PF ≥ 0.50
Input / Output	AC 220-240V 50-60Hz · DC 200mA
Protection / Class	IP20 · Class II · Cut-out Ø75 mm

ACCESSORIES Options




- ☐ White housing
- ☒ Black housing
- ☐ Dimmable driver: Triac / 0-10V / DALI
- ☐ Optional lens / anti-glare accessories



COLOR TEMPERATURE




BEAM ANGLE



USAGE SPACES

- HOME** Residential accent lighting
- RETAIL** Shops & commercial spaces
- HOTEL** Hospitality & galleries

DIMENSIONS & PACKAGING unit: mm (untoleranced dimensions ±0.5 mm)



Ceiling cut-out: Ø75 mm
Inner box: 10 × 10 × 7 cm
Carton: 42 × 32 × 30 cm · 48 pcs/ctn
Net weight: 0.18 kg/pc