

Laboratory and Equipment

Test lab	n/a
Spectrometer Manufacturer and Model	n/a, n/a – n/a
Measurement date	6/25/2026

Measurement Conditions

Tested c-planes	8
Tested gamma angles	181 – 1.00°
Input Power	10.64 W


Tested Light Source

Luminaire	2021/12/23 17:46:24
Basic Luminous Shape	PANEL
Item No.	
Manufacturer	Moon On Noon


Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	756.4 lm – 0.0003% / 100%
Efficiency	71.09 lm/W
Peak Intensity	1733 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index	CRI 85.0

Polar light distribution diagram




Beam details




Luminaire budgetary diagram


LAMPS (number of lamps)




Iso-intensity Diagram (Iso-candela)



Iso-illuminance Diagram (Iso-lux)




Linear intensity distribution diagram



IESNA TM-15-07 Luminaire Classification System For Outdoor Luminaires

BUG rating B1 U0 G0



Forward Light

Low (0-30°)	301.1 lm	39.8%
Medium (30-60°)	82.8 lm	10.9%
High (60-80°)	13.7 lm	1.8%
Very High (80-90°)	1.0 lm	0.1%

Back Light

Low (0-30°)	277.2 lm	36.6%
Medium (30-60°)	64.8 lm	8.6%
High (60-80°)	14.6 lm	1.9%
Very High (80-90°)	1.5 lm	0.2%

Uplight

Low (90-100°)	0.0 lm	0.00%
High (100-180°)	0.0 lm	0.0%

Total

Sum	756.4 lm	100,0%
-----	----------	--------